

# MIX and Match

BY AMIT MAVALANKAR, PE, JAMES J. BONANNO, PE,  
AND STEPHEN V. DESIMONE, PE

A new mixed-use  
development is boosting  
one of New York's most  
prominent business districts  
while working to blend in  
with its existing neighbors.



**Amit Mavalankar**

([amit.mavalankar@de-simone.com](mailto:amit.mavalankar@de-simone.com)) is a senior project manager,

**James J. Bonanno**

([james.bonanno@de-simone.com](mailto:james.bonanno@de-simone.com)) is a principal and **Stephen V. DeSimone**

([Stephen.desimone@de-simone.com](mailto:Stephen.desimone@de-simone.com)) is president, all with DeSimone Consulting Engineers.





- ▲ A rendering of the overall complex.
- ▶ Phase 1 of the project uses 4,500 tons of steel.
- ▼ The residential building is at left and the commercial building at right.



**DOWNTOWN FLUSHING IN QUEENS** is the fourth-largest central business district in New York—nothing to sneeze at in a city of 8.4 million.

As the epicenter of Flushing—a neighborhood of roughly 72,000 residents—the area is a stone’s throw from Flushing Meadows Corona Park, home of the USTA Billie Jean King National Tennis Center, and the New York Mets’ Citi Field.

Currently rising from its center is a 1.8-million-sq.-ft complex known as Flushing Commons. The mixed-use project is organized into four components comprising a residential building and office, retail, parking and com-

munity space in a total of five distinct buildings. Phase I is a development of approximately 670,000 sq. ft, with a 14-story residential tower and an 11-story office building, both steel-framed. Underneath the buildings is a concrete-framed four-story, 270,000-sq.-ft below-grade garage with 980 parking spaces.

The massive project achieved its first milestone this past spring with the topping out of the residential tower and the office building. Using 4,500 tons of structural steel, Phase I is expected to be completed early next year, with the entire project scheduled to open by 2021.





◀ Comprising 1.8 million sq. ft, the entire project will feature a total of five distinct buildings once complete.

### Residential

Designing a mixed-use residential tower is never an easy or straightforward task, as the column grids for parking and retail portions do not typically synch with the column spacing for the residential units. The columns for the residential units are usually located within the room layouts at locations where they may be most easily camouflaged by architectural elements, and trying to match them with the commercial column grids often imposes constraints on floor layout. The design team looked to the Girder-Slab system to address this issue. The system is an assembly of asymmetrical steel beams referred to as “D-Beams” and is fabricated from a standard rolled wide-flange section and a flat bar. It supports a hollow-core pre-cast plank on its bottom flange.



◀ Planks over the D-Beams for a typical residential floor, prior to grouting.



**AWS**  
American Welding Society®  
PUBLICATIONS  
aws.org

**WELDING HANDBOOK**  
Materials and Applications, Part 2

## Own Expert Knowledge. Own the *Welding Handbook Series*.

This comprehensive multi-volume *Welding Handbook* set is a must-have resource for structural engineers, designers, and fabricators. Within its five-volumes of content exists the largest body of knowledge on welding available anywhere. This one-of-a-kind series covers the entire spectrum of welding from science and technology, welding processes and safety to materials and applications. Its extensive illustrations, charts, diagrams and maps, ensure you have the most concise, comprehensive body of work, written and backed by leading scientists, engineers, and educators.

Your chance to own expert knowledge is here. The *Welding Handbook* is available by volume, chapter or as a series.


To purchase or preview online visit [go.aws.org/WHBseries](http://go.aws.org/WHBseries).

## Connect Steel to Steel without Welding or Drilling


- Full line of high-strength fasteners
- Ideal for secondary steel connections and in-plant equipment
- Easy to install or adjust on site
- Will not weaken existing steel or harm protective coatings
- Guaranteed Safe Working Loads
- Corrosion resistant



*FloorFix and Grating Clip secure raised or open floors and grating.*



*We manufacture ICC-ES certified BoxBolt® for HSS blind connections.*



**LNA SOLUTIONS**  
A KEE SAFETY COMPANY

For a catalog and pricing, call toll-free 1-888-724-2323 or visit [www.LNAsolutions.com/BC-1](http://www.LNAsolutions.com/BC-1)





got rust?



they don't!

Even **stadiums** are best when hot dip galvanized! After all, where would you rather sit your family with thousands of other screaming, jumping fans? Let V&S show you how to be **RUST-FREE** on your next project! Architects, Engineers and DOT's are specifying **hot dip galvanizing** for corrosion protection of steel more than ever before.

Now available -- The new AIA-accredited **Sustainable Development Seminar** from the American Galvanizers Association. Call us to schedule your personal luncheon seminar at your location.

Hot Dip Galvanizing!  
Saving Our Infrastructure

*"One Dip At A Time"*



*"Zinc Protects Steel"*

800-801-3648

[www.HotDipGalvanizing.com](http://www.HotDipGalvanizing.com)

Locations to Serve you:

Perth Amboy, NJ

Columbus, OH

New Castle, DE


Detroit, MI

Jonestown, PA

Memphis, TN

Taunton, MA





Girder-Slab Technologies

▲ A rendering of the Girder-Slab System



▲ Construction of the residential building.

The gravity system for the residential building incorporates D-Beams for the typical residential levels to support 4-ft-wide, 8-in.-deep planks that span 28 ft, which matched the column spacing in the retail levels and parking garage. In the other direction, the beams span 18 ft to 20 ft between the W12 columns. The lateral force-resisting system was designed to react to wind loads and consists of concentrically braced frames around the stair and elevator core, using brace and column sizes up to W14×370. The system is predominantly drift-controlled, and fewer braced frames were used to control the overall as well as inter-story drift. The lateral shear forces from the steel braced frames are transferred to the concrete shear walls by strap beams.

The residential tower's facade appears as a window wall, blending the brick and glass to form a typical residential look that fits in with the surrounding neighborhood. The facade panels are supported from the edge of the floor system and are attached to perim-

eter W10 beams in the north-south direction and specially designed solid precast plank with embeds in the east-west direction.

### Commercial and Office

The gravity system for the commercial building consists of conventional composite wide-flange steel beams carrying 3-in. metal deck with 3¼-in.-thick lightweight topping concrete. The beams in turn are supported by W14 columns. The parking column grid of 30 ft by 28 ft is also used for the retail and office floors above. As with the residential tower, the lateral force-resisting system consists of concentrically braced frames around the stair and elevator cores to resist wind loads, and uses wide-flange braces and column elements. Larger wide-flange sections were used to limit the inter-story drifts. The lateral system is drift-controlled, and fewer brace frames were used at limited locations to keep the design in line with the architect's requirements.

- ▼ Phase 1 includes a 14-story residential tower and an 11-story office building, both steel-framed, on top of a four-story, 270,000-sq.-ft below-grade garage with 980 parking spaces.







# MORE THAN STEEL JOISTS & DECK

## High-performance steel building systems

Speed erection time, achieve architectural vision, and reduce total-project costs. We are your nationwide resource for the design, manufacture and delivery of roofing and flooring systems. Exposed surfaces and acoustical applications enabled by architectural ceiling and cladding systems. Unmatched time and cost savings for multi-story construction projects with Versa-Floor™ long-span composite floor systems.

- Structural roofing and flooring systems
- Architectural ceiling and cladding systems
- Long-span composite floor systems

Learn more at: [newmill.com/expand](http://newmill.com/expand)



**NEW MILLENNIUM**  
BUILDING SYSTEMS

**Building a better steel experience.**





◀ Construction of the 11-story office tower.

The facade consists of brick panels at the retail floors and high-performance curtain wall and patches of brick veneer at the commercial floors. The prefabricated panels are hung from the perimeter slab edges, and  $\frac{5}{16}$ -in.-thick to  $\frac{1}{2}$ -in.-thick steel plates cantilever from the top flanges of the perimeter beams to receive the embed plates for the various facade attachments.

### Construction Coordination

The architect and engineers used 3D building information modeling (BIM) to coordinate the design with various other disciplines. The use of a Revit model in the preliminary phases of design facilitated early coordination between different trades and resolve clashes between structural and MEP components. The steel fabricator used Tekla to model the steel-framed buildings. This helped the general contractor coordinate the strap beams, concrete podium and facade embeds to support the panelized facade system with the structural interfaces. The contractor and design team used Autodesk's Constructware as a submittal tracking system, which helped smoothen the construction administration process.

This level of coordination, over a project with so many components and in a tight urban setting, is impressive but also expected for such a high-profile development at the heart of New York's largest and second-most populous borough. ■

### Owners

F & T Group, The Rockefeller Group, AECOM Capital

### General Contractor

Tishman Construction, New York


### Architect

Perkins Eastman Architects, New York

### Structural Engineer

DeSimone Consulting Engineers, New York

### Steel Fabricator, Erector and Detailer

Berlin Steel Construction Co.,  Kensington, Conn.



▲ A strap beam erected on-site.



◀ A Revit model of Phase 1.